

## FK-525

### 10 M IR Color Waterproof Camera



#### Feature

- 10 M IR Color Waterproof Camera
- 1/4" SHARP Color CCD
- IR View Distance up to 10 meters
- Waterproof suitable for Indoor and Outdoor use
- Auto Backlight Compensation

#### Specifications

Pick-up Device	<input type="checkbox"/>	<input type="checkbox"/>	1/4" SHARP Color CCD
Picture Elements	<input type="checkbox"/>	<input type="checkbox"/>	512(H)X582(V) Pixels
Horizotal Resolution	<input type="checkbox"/>	<input type="checkbox"/>	400 TV Lines
Standard Board Lens	<input type="checkbox"/>	<input type="checkbox"/>	4 mm.
Minimum Illumination	<input type="checkbox"/>	<input type="checkbox"/>	0Lux / F1.2 (When IR On)
Auto Gain Control	<input type="checkbox"/>	<input type="checkbox"/>	Yes
Auto White Balance	<input type="checkbox"/>	<input type="checkbox"/>	Yes
Backlight compensation	<input type="checkbox"/>	<input type="checkbox"/>	Auto
Electronic Shutter	<input type="checkbox"/>	<input type="checkbox"/>	1/50 (1/60 - 100,000 sec.)
S/N Ratio	<input type="checkbox"/>	<input type="checkbox"/>	More than 48dB
Gamma Correction	<input type="checkbox"/>	<input type="checkbox"/>	>0.45
Operating Temperature	<input type="checkbox"/>	<input type="checkbox"/>	-20C - 50C
Sync System	<input type="checkbox"/>	<input type="checkbox"/>	Internal
Video Output	<input type="checkbox"/>	<input type="checkbox"/>	1.0Vp-p / 75 Ohms
Power Supply	<input type="checkbox"/>	<input type="checkbox"/>	DC12V
Power Consumption	<input type="checkbox"/>	<input type="checkbox"/>	120mA (280mA When IR On)
Effective Range	<input type="checkbox"/>	<input type="checkbox"/>	10 - 15 meters
Dimension (mm)	<input type="checkbox"/>	<input type="checkbox"/>	99(L)X71(W)X169(H)
Weight	<input type="checkbox"/>	<input type="checkbox"/>	508g

\*Design and specifications are subject to change without notice